

ALUMINIUM CONDUCTOR CABLES

◆ BUILDING WIRES AND CABLES ◆

CONTENTS

PAGE

THWA 750 V 70°C ALUMINIUM CONDUCTOR PVC INSULATED,
SINGLE CORE (TIS 293-2541)

100

THWA-C 750 V 70°C COMPACTED ALUMINIUM CONDUCTOR PVC INSULATED,
SINGLE CORE (TIS 293-2541)

101

ALUMINIUM CONDUCTOR CABLES
BUILDING WIRES AND CABLES

750 V 70°C ALUMINIUM CONDUCTOR PVC INSULATED, SINGLE CORE


CABLE STRUCTURE		TECHNICAL DATA	
Conductor	: Solid and stranded hard drawn aluminium wires Size 10 mm ² up to 500 mm ²	Classification	: Maximum conductor temperature 70°C : Circuit voltage not exceeding 750 Volts
Insulation	: Polyvinyl chloride (PVC) Color : Black	Testing voltage	: 2,500 Volts
		Reference standard	: TIS 293-2541, Table 1
APPLICATION			
For aerial cable (Service & Main)			

Nominal cross sectional area (mm ²)	Number and diameter of wires (No./mm)	Insulation thickness nominal (mm)	Overall diameter approx. (mm)	Conductor resistance at 20°C maximum (Ω/km)	Insulation resistance at 70°C minimum (MΩ-km)	Breaking strength of conductor minimum (N)	continuous current rating in free air maximum (A)	Cable weight approx. (kg/km)	Standard length (m)
10	1/3.49	1.1	6.0	3.08	0.0078	1,562	52	50	500/C
10	7/1.32	1.1	6.5	3.08	0.0070	1,769	52	55	500/C
16	1/4.43	1.1	7.0	1.91	0.0064	2,445	70	70	500/C
16	7/1.68	1.1	7.6	1.91	0.0058	2,781	70	80	500/C
25	7/2.12	1.3	9.3	1.20	0.0055	4,241	95	120	300/C
35	7/2.49	1.3	10.5	0.868	0.0048	5,703	117	160	200/C
50	7/2.90	1.5	12.0	0.641	0.0047	7,423	143	210	200/C
50	19/1.76	1.5	12.5	0.641	0.0047	8,114	143	210	200/C
70	19/2.12	1.5	14.0	0.443	0.0040	11,487	185	280	100/C
95	19/2.49	1.7	16.5	0.320	0.0038	15,470	226	390	100/C
120	19/2.80	1.7	18.0	0.253	0.0035	18,810	264	470	500/D
120	37/2.01	1.7	18.0	0.253	0.0034	20,114	264	470	500/D
150	37/2.23	1.9	20.0	0.206	0.0035	24,704	302	600	500/D
185	37/2.50	2.1	22.0	0.164	0.0034	30,187	352	700	500/D
240	61/2.23	2.3	25.0	0.125	0.0033	38,568	421	900	500/D
300	61/2.49	2.5	28.0	0.100	0.0032	46,901	487	1,100	500/D
400	61/2.82	2.7	32.0	0.0778	0.0031	57,948	574	1,400	500/D
500	61/3.20	3.1	36.0	0.0605	0.0031	73,194	675	1,900	500/D

C : Packing in coil
D : Packing in drum

THWA-C



750 V 70°C COMPACTED ALUMINIUM CONDUCTOR PVC INSULATED, SINGLE CORE



CABLE STRUCTURE

Conductor : Compact stranded hard drawn aluminium wires
 Sizes 10 mm² up to 500 mm²

Insulation : Polyvinyl chloride (PVC)
 Color : Black

TECHNICAL DATA

Classification : Maximum conductor temperature 70°C
 : Circuit voltage not exceeding 750 Volts

Testing voltage : 2,500 Volts
Reference standard : TIS 293-2541, Table 2

APPLICATION

For aerial cable (Service & Main)

Nominal cross sectional area (mm ²)	Actual cross sectional area (mm ²)	Minimum number of wires (No.)	Compact conductor diameter approx. (mm)	Insulation thickness nominal (mm)	Overall diameter approx. (mm)	Conductor resistance at 20° C maximum (Ω/km)	Insulation resistance at 70°C minimum (MΩ-km)	Breaking strength of conductor minimum (N)	Continuous current rating in free air maximum (A)	Cable weight approx. (kg/km)	Standard length (m)
10	9.64	6	3.72	1.1	6.3	3.08	0.0084	1,768	52	50	500/C
16	15.55	6	4.69	1.1	7.2	1.91	0.0068	2,734	69	75	500/C
25	24.75	6	5.90	1.3	8.8	1.20	0.0064	4,120	93	110	300/C
35	34.21	6	6.95	1.3	9.9	0.868	0.0056	5,591	115	150	300/C
50	46.32	6	8.01	1.5	11.5	0.641	0.0059	7,313	141	200	200/C
70	67.03	12	9.73	1.5	13.5	0.443	0.0050	10,420	178	270	100/C
95	92.79	15	11.40	1.7	15.5	0.320	0.0047	14,098	220	370	100/C
120	117.37	15	12.95	1.7	17.0	0.253	0.0042	18,518	258	450	100/C
150	144.15	15	14.27	1.9	18.5	0.206	0.0042	22,457	294	550	500/D
185	181.06	30	15.98	2.1	21.0	0.164	0.0042	28,974	342	700	500/D
240	237.55	30	18.47	2.3	24.0	0.125	0.0040	37,506	410	900	500/D
300	296.94	30	20.68	2.5	26.0	0.100	0.0038	45,642	475	1,100	500/D
400	381.67	53	23.39	2.7	30.0	0.0778	0.0036	56,992	560	1,400	500/D
500	490.81	53	26.67	3.1	34.0	0.0605	0.0037	72,195	659	1,800	500/D

C : Packing in coil
 D : Packing in drum

